NextGen Scientific Publication
International Conference on Emerging Trends in Engineering, Technology, and Innovation (ICETETI-2024)

Pg. No. 140-161, ICETETI24-110, 2024
https://doi.org/10.63282/3117-5481/ICETETI24-110
Conference Date: 30th August 2024

Original Article

Intelligent DevSecOps Optimization Using Machine Learning-Based Vulnerability Prediction and Automated Security Assessment in CI/CD Pipelines

***Sathishkumar**
J.J. College of Engineering and Technology, Trichy.

Abstract:

The rapid adoption of cloud-native applications, microservices, and CI/CD pipelines has increased software delivery efficiency while introducing significant security challenges, including vulnerable source code, insecure dependencies, misconfigurations, and software supply chain attacks. Traditional security assessment methods often rely on predefined rules and reactive remediation, limiting their effectiveness in dynamic development environments. This research proposes an intelligent DevSecOps optimization framework that integrates machine learning-based vulnerability prediction with automated security assessment throughout the CI/CD lifecycle. The framework combines source code analysis, dependency intelligence, software complexity metrics, container configurations, and historical vulnerability data using machine learning techniques such as Random Forest, Gradient Boosting, and Support Vector Machines. It incorporates SAST, SCA, DAST, IaC scanning, container security assessment, SBOM generation, and automated policy enforcement. An intelligent risk prioritization mechanism evaluates vulnerability severity, exploitability, asset criticality, and remediation complexity to support effective security decisions. The proposed framework aims to enhance vulnerability detection, automate security assessment, improve remediation prioritization, and strengthen software supply chain security while maintaining efficient and reliable software delivery.

Keywords:

DevSecOps, Machine Learning, Vulnerability Prediction, CI/CD Pipeline Security, Automated Security Assessment, Software Vulnerability Detection, Random Forest, Deep Learning, SAST, SCA, DAST, Software Supply Chain Security, Predictive Cybersecurity, Continuous Integration, Continuous Deployment.

1. Introduction

The continuous evolution of software engineering practices has fundamentally changed how enterprise applications are designed, developed, tested, distributed, and maintained. Organizations increasingly adopt Agile methodologies, cloud-native development, microservices architectures, containerization, and automated deployment technologies to accelerate software delivery and improve operational flexibility. Within this environment, Continuous Integration and Continuous Deployment (CI/CD) pipelines provide the automation infrastructure required to transform source code changes into deployable software artifacts. These pipelines

Copyright by the Author(s). This work is licensed under a Creative Commons Attribution-ShareAlike 4.0 International (CC BY-NC-ND 4.0) License (https://creativecommons.org/licenses/by-sa/4.0/)

support frequent integration, automated testing, application packaging, infrastructure provisioning, and deployment across development, testing, staging, and production environments.

Although CI/CD automation improves development efficiency, it also introduces additional security responsibilities. Modern software applications frequently depend on external libraries, open-source frameworks, container images, third-party APIs, cloud services, and infrastructure configuration templates. Each dependency and integration point introduces a potential attack surface. A vulnerability in a commonly used library, an insecure container configuration, an exposed authentication credential, or an incorrectly configured pipeline permission can compromise an application or its underlying delivery infrastructure. Consequently, application security can no longer be treated as an independent activity performed immediately before production deployment. Security assessment must become an integral component of the entire software development lifecycle.

DevSecOps represents an evolutionary extension of DevOps that integrates security responsibilities into development and operational processes. Rather than treating security as a final approval activity, DevSecOps promotes continuous security testing, automated policy enforcement, collaborative vulnerability remediation, and security monitoring throughout the software delivery process. The National Institute of Standards and Technology (NIST) emphasizes the importance of integrating software supply chain security practices into CI/CD pipelines, including artifact integrity, provenance, dependency management, and secure development activities (Chandramouli et al., 2024). Similarly, the NIST Secure Software Development Framework provides structured recommendations for reducing software vulnerabilities and addressing security weaknesses throughout software development (Souppaya et al., 2022).

Despite these developments, conventional DevSecOps implementations continue to face several operational limitations. Many organizations integrate multiple security scanners into their CI/CD pipelines, but these tools frequently operate independently and generate findings without sufficient contextual correlation. For example, a static code analyzer may identify a potentially unsafe function, while a dependency scanner reports a vulnerable library and a container scanner identifies an outdated operating system package. Although each finding may be technically relevant, the combined security implications are not always evaluated consistently. Security engineers must manually correlate findings, investigate exploitability, determine business impact, and prioritize remediation activities.

Another significant challenge is the increasing volume of security findings generated by automated assessment tools. Large software repositories may contain thousands of source files, extensive dependency trees, multiple container images, and numerous infrastructure configuration files. Repeated scanning can generate large numbers of alerts, including false positives, duplicate findings, and vulnerabilities with limited practical exposure. When development teams receive excessive security notifications, remediation activities may become inefficient, and critical findings may be overlooked.

Machine learning offers an opportunity to improve this situation by identifying patterns associated with previously discovered vulnerabilities and predicting which software components are more likely to contain security weaknesses. Instead of depending exclusively on predefined detection signatures, machine learning models can examine historical vulnerability records, source code characteristics, software complexity, development activity, and dependency relationships. These models can produce predictive risk assessments that guide security testing toward components requiring greater attention.

Research in software vulnerability prediction has investigated the use of statistical learning, traditional machine learning, and deep learning to identify vulnerable software components. A systematic review by the IEEE Access research community identified substantial use of machine learning and deep learning techniques in vulnerability prediction, while highlighting issues related to datasets, feature selection, imbalance handling, and model evaluation (A Systematic Literature Review on Software Vulnerability Prediction Models, 2023). Similarly, the systematic mapping study by Kalouptsoglou et al. (2023) identified cross-project generalization and model explainability as important continuing research challenges.

The integration of machine learning into DevSecOps should therefore extend beyond simply adding a predictive model to an existing security scanner. An effective solution requires a coordinated architecture connecting vulnerability prediction, automated security assessment, risk prioritization, remediation recommendations, and deployment governance. Predictive outputs must be correlated with actual scanner findings rather than being treated as definitive evidence of exploitable vulnerabilities. This distinction is

particularly important because a machine learning prediction represents an estimated probability or risk category, whereas a confirmed security finding requires technical validation.

This research introduces an intelligent DevSecOps optimization framework that combines predictive vulnerability analysis with automated security assessment across CI/CD pipelines. The framework is designed to support early identification of potentially vulnerable components, intelligent selection of security assessment activities, contextual prioritization of findings, and controlled deployment decisions.

1.1. Research Problem

Traditional CI/CD security implementations primarily depend on rule-based security scanners, signature databases, vulnerability severity classifications, and manually configured pipeline policies. Although these mechanisms provide important detection capabilities, they frequently lack predictive intelligence and comprehensive risk correlation.

The central research problem concerns the absence of a unified mechanism that can combine historical vulnerability patterns, source code characteristics, dependency information, and real-time security assessment results to predict vulnerable components and optimize security activities within automated software delivery pipelines.

The proposed research addresses the following challenges:

- Limited predictive identification of vulnerable source code before conventional security testing identifies an issue.
- Excessive security alerts resulting from independent scanning tools and insufficient contextual prioritization.
- Difficulty correlating source code vulnerabilities, dependency weaknesses, container risks, and infrastructure misconfigurations.
- Limited generalization of vulnerability prediction models across different projects, programming languages, and software architectures.
- Inadequate integration of explainable machine learning predictions with automated security policies and deployment decisions.
- Operational risks arising from insufficient protection of CI/CD credentials, build agents, artifacts, and pipeline permissions.

1.2. Research Objectives

The primary objective is to develop an intelligent and integrated DevSecOps framework that improves vulnerability prediction and automated security assessment in CI/CD pipelines.

The specific objectives are:

- To investigate machine learning techniques suitable for predicting potentially vulnerable software components using historical and code-level information.
- To design a predictive security architecture that integrates vulnerability intelligence with CI/CD workflows.
- To combine SAST, SCA, DAST, IaC scanning, and container security assessment into a coordinated assessment mechanism.
- To develop a risk prioritization approach that considers vulnerability severity, exploitability, application exposure, and business criticality.
- To investigate explainable machine learning techniques for improving transparency and developer trust.
- To establish automated security gates that support risk-based deployment approval, remediation, and escalation.
- To define an evaluation methodology for measuring prediction effectiveness, assessment efficiency, and CI/CD operational impact.

1.3. Research Contributions

The principal contributions of this research are:

- Predictive vulnerability intelligence: Integration of machine learning models with software development characteristics and historical vulnerability records.
- Unified security assessment: Correlation of multiple automated security testing mechanisms within a common CI/CD architecture.
- Intelligent risk prioritization: Context-aware classification of vulnerabilities based on technical and operational importance.

- Explainable security decisions: Incorporation of feature importance and explanation mechanisms to support security investigation.
- Automated deployment governance: Establishment of risk-based security gates that distinguish confirmed vulnerabilities from predictive warnings.
- Continuous learning architecture: Introduction of a controlled model feedback mechanism using validated vulnerability and remediation information.

1.4. Research Significance

The proposed research is relevant to organizations developing enterprise applications, cloud-native platforms, financial systems, healthcare applications, e-commerce services, and distributed software environments. These systems require frequent software releases while maintaining strong security assurance.

By combining predictive analysis with automated assessment, organizations can potentially reduce unnecessary scanning effort, identify high-risk components earlier, and allocate security engineering resources more effectively. The framework also supports a transition from reactive vulnerability management toward proactive and continuous security governance.

2. Literature Review

2.1. Evolution of DevSecOps and Continuous Security Integration

The evolution of DevOps has encouraged organizations to establish automated workflows that connect software development and IT operations. DevOps emphasizes continuous integration, continuous delivery, collaboration, infrastructure automation, and rapid feedback. However, the increasing dependence on automated development infrastructure has created a requirement for stronger security integration. DevSecOps addresses this requirement by incorporating security controls into development and operational workflows rather than positioning security as an isolated testing activity.

The fundamental principle of DevSecOps is that security responsibilities should be distributed across the software development lifecycle. Developers are expected to follow secure coding practices, security engineers establish assessment policies, and operations teams maintain secure deployment environments. Automated testing tools provide continuous feedback regarding vulnerabilities, configuration weaknesses, and compliance violations.

Souppaya et al. (2022), through NIST Special Publication 800-218, established the Secure Software Development Framework (SSDF), which provides structured practices for reducing vulnerabilities and mitigating the impact of undetected security weaknesses. The framework emphasizes secure development environments, protection of software components, vulnerability identification, and continuous improvement. These principles provide an important foundation for the proposed intelligent DevSecOps architecture.

Chandramouli et al. (2024) further examined the integration of software supply chain security into DevSecOps CI/CD pipelines. Their work emphasizes the importance of artifact integrity, provenance, software component identification, and security assurance throughout the software delivery process. This demonstrates that application security must extend beyond source code inspection to include the infrastructure and processes responsible for building and distributing software.

Nevertheless, conventional DevSecOps implementations frequently depend on independently configured security tools. Although these tools provide valuable detection capabilities, they may generate disconnected results and lack predictive capabilities. An intelligent DevSecOps architecture should therefore integrate security assessment outputs into a shared decision-making environment.

2.2. Machine Learning-Based Software Vulnerability Prediction

Software vulnerability prediction refers to the identification of software components that exhibit characteristics associated with previously discovered security weaknesses. Unlike conventional vulnerability detection, which primarily identifies known or observable security problems, predictive analysis estimates the likelihood that a component may contain a vulnerability based on historical patterns and measurable characteristics.

Machine learning models can analyze different categories of software information, including source code complexity, programming constructs, dependency characteristics, development history, commit frequency, and previously identified vulnerabilities. These characteristics can be transformed into structured features for training predictive classifiers.

Bassi and Singh (2023) conducted a systematic literature review of software vulnerability prediction models published between 2000 and 2022. Their research identified extensive use of traditional machine learning and deep learning methods, together with important considerations involving feature selection, dataset balancing, preprocessing, and evaluation. Their findings demonstrate that vulnerability prediction is a substantial research area, although selecting appropriate datasets and evaluation methods remains challenging.

Traditional algorithms such as Random Forest, Decision Trees, Support Vector Machines, Logistic Regression, and Gradient Boosting are particularly useful when the input data consists of structured software metrics. These algorithms can classify source files, classes, methods, or components into risk categories. Random Forest is valuable because it combines multiple decision trees and can capture nonlinear relationships among software characteristics. Gradient Boosting can improve predictive performance by progressively correcting classification errors, while Support Vector Machines can identify decision boundaries in complex feature spaces.

Deep learning introduces additional capabilities by learning representations from source code and contextual information. Neural architectures can analyze token sequences, abstract syntax trees, control-flow representations, and relationships between program statements. These representations can provide information that may not be fully captured by conventional software metrics.

Kalouptsoglou et al. (2023) examined 180 primary studies concerning software vulnerability prediction and identified increasing interest in deep learning and textual source code representations. Their study also highlighted the limited attention given to cross-project prediction, indicating that models developed using one project may not perform consistently when transferred to another.

2.3. Source Code-Based Vulnerability Analysis

Source code analysis represents one of the most important components of automated software security. Vulnerabilities may originate from insecure input handling, incorrect authentication mechanisms, unsafe memory operations, inadequate validation, improper exception handling, and insecure cryptographic implementations.

Traditional static analysis examines source code without executing the application. It identifies potentially dangerous programming patterns through predefined rules, data-flow analysis, control-flow analysis, and semantic inspection. Although static analysis can detect many common vulnerability patterns, its effectiveness depends on the completeness of its rules, language support, and the context available to the analysis engine.

Machine learning extends source code analysis by identifying statistical and semantic patterns associated with vulnerable implementations. For example, a model may learn that certain combinations of complex control structures, unsafe API usage, insufficient validation, and historically vulnerable code patterns are associated with increased security risk.

However, source code prediction must be distinguished from confirmed vulnerability detection. A function predicted as high-risk does not necessarily contain an exploitable weakness. Therefore, predictive models should direct additional assessment rather than independently establish security violations.

The research literature also demonstrates the importance of dataset quality. Vulnerability labels obtained from public repositories may be incomplete, inconsistent, or incorrectly associated with source code changes. Consequently, reliable model development requires careful mapping between vulnerability advisories, affected versions, code commits, and the corresponding software components.

2.4. Automated Security Assessment in CI/CD Pipelines

Automated security assessment involves the continuous examination of application code, dependencies, deployment configurations, infrastructure definitions, and running application behavior. Different testing approaches address different categories of security weaknesses.

Static Application Security Testing examines source code to identify potentially insecure programming practices before execution. Software Composition Analysis identifies vulnerable third-party dependencies, outdated libraries, licensing concerns, and transitive dependency risks. Dynamic Application Security Testing examines running applications by interacting with exposed interfaces and observing their responses. Interactive Application Security Testing can combine runtime behavior with application execution information.

Infrastructure as Code scanning evaluates infrastructure configuration templates for insecure permissions, publicly exposed resources, weak encryption settings, and other deployment weaknesses. Container security assessment examines base images, operating system packages, application dependencies, image configuration, and runtime privileges.

The OWASP DevSecOps guidance identifies SAST, SCA, DAST, IaC scanning, software supply chain security, compliance checks, and automated security gates as important elements of an integrated DevSecOps process (OWASP Foundation, n.d.). These capabilities demonstrate that security assessment must cover the complete delivery environment rather than source code alone.

The OWASP Top 10 CI/CD Security Risks project additionally identifies weaknesses such as insufficient flow control, inadequate identity and access management, dependency chain abuse, poisoned pipeline execution, poor credential hygiene, insecure configuration, improper artifact integrity validation, and insufficient logging (OWASP Foundation, n.d.). These risks establish the need to secure both the application and the pipeline responsible for delivering it.

2.5. Intelligent Vulnerability Prioritization

One of the major limitations of conventional vulnerability management is the reliance on severity scores as the primary basis for remediation decisions. Although severity classifications provide useful information, they do not always reflect the actual risk presented by a vulnerability in a particular deployment environment.

A vulnerability with a high severity score may affect a component that is not reachable in production, while a vulnerability with a comparatively lower severity score may exist in an internet-facing authentication service. Therefore, effective prioritization should consider exploitability, exposure, asset criticality, available remediation options, and environmental context.

The proposed framework combines machine learning predictions with established vulnerability intelligence and contextual security information. Common Vulnerability Scoring System (CVSS) assessments can provide severity information, while the Exploit Prediction Scoring System (EPSS) can contribute information concerning the estimated probability of exploitation. The CISA Known Exploited Vulnerabilities catalog can provide additional evidence of vulnerabilities known to be exploited in real-world environments.

These information sources should not be treated as interchangeable. CVSS describes vulnerability severity, EPSS estimates exploitation likelihood, and a machine learning model estimates vulnerability propensity from software characteristics. Combining these perspectives can support a more comprehensive security decision.

2.6. Research Gaps

The reviewed literature identifies several research gaps relevant to intelligent DevSecOps optimization.

First, vulnerability prediction research frequently concentrates on identifying vulnerable files or components without examining how predictions can influence automated CI/CD security workflows. A predictive result becomes more operationally valuable when it can automatically determine which security assessments should be performed and when additional investigation is required.

Second, many security scanners operate independently and produce findings in different formats. The lack of consistent correlation between source code findings, dependency vulnerabilities, container risks, and infrastructure weaknesses can limit the accuracy of overall risk assessment.

Third, cross-project generalization remains a significant challenge. A model trained on one software ecosystem may encounter different coding practices, programming languages, dependency structures, and vulnerability distributions in another environment.

Fourth, explainability is essential for practical adoption. Development teams require understandable explanations for why a component is classified as high-risk. Predictions that cannot be interpreted may reduce developer confidence and increase resistance to automated security policies.

Fifth, predictive models are vulnerable to data leakage, class imbalance, outdated training data, and concept drift. These problems can produce misleading performance measurements or deteriorating predictions when software ecosystems change.

Finally, research must address the security of the machine learning infrastructure and CI/CD platform itself. A predictive security service with excessive repository permissions or access to deployment credentials may become another attack surface.

The proposed research addresses these gaps through an integrated architecture combining predictive analysis, automated security testing, contextual risk prioritization, explainability, and controlled deployment governance.

Table 1. Comparative Analysis of Existing Security Approaches and the Proposed Intelligent DevSecOps Framework

Security approach	Primary capability	Main limitation	Proposed improvement
Rule-based SAST	Detects insecure source code patterns	Depends on predefined rules	Prioritizes code requiring additional assessment
SCA	Identifies vulnerable dependencies	Limited understanding of application-specific context	Correlates dependency findings with application exposure
DAST	Identifies runtime application weaknesses	Requires an executable application	Uses predictive information to guide targeted testing
IaC scanning	Identifies infrastructure misconfigurations	Primarily evaluates configuration rules	Combines configuration risks with deployment context
Traditional vulnerability management	Classifies and tracks known vulnerabilities	Frequently reactive	Introduces predictive vulnerability intelligence
Conventional DevSecOps	Integrates security tools into CI/CD	May produce disconnected security results	Establishes unified security correlation and governance
Proposed intelligent framework	Combines prediction, scanning, and risk-based decisions	Requires model governance and validation	Supports continuous predictive and preventive assessment

3. Research Methodology

3.1. Research Design

This research adopts a design-oriented research methodology to develop an integrated intelligent DevSecOps optimization framework. The methodology focuses on identifying practical security challenges, examining existing technical approaches, designing an integrated architecture, defining predictive modeling mechanisms, and establishing an evaluation strategy.

The research does not claim experimentally measured improvements or present fabricated model accuracy values. Instead, it establishes a technically grounded framework and an empirical validation methodology that can be implemented and evaluated using real-world software repositories and CI/CD environments.

The research process consists of five major phases: problem identification, data preparation, predictive model development, automated security integration, and performance evaluation. The proposed methodology is designed to support both academic experimentation and practical enterprise implementation.

3.2. Proposed Framework Architecture

The framework consists of six interconnected architectural layers.

3.2.1. Source Code and Development Data Layer

This layer collects information from source code repositories, development commits, pull requests, software dependency manifests, historical security findings, and issue tracking systems. The collected information provides the foundation for vulnerability prediction.

3.2.2. Feature Engineering and Data Preparation Layer

The collected data is transformed into structured features representing source code complexity, programming constructs, dependency information, change frequency, and previous vulnerability patterns. Data cleaning, normalization, feature selection, and class imbalance handling are performed before model training.

3.2.3. Machine Learning Prediction Layer

This layer applies supervised machine learning algorithms to estimate vulnerability propensity at file, function, class, or component level. The prediction engine produces risk classifications and interpretable feature contributions.

3.2.4. Automated Security Assessment Layer

The assessment layer integrates SAST, SCA, DAST, IaC scanning, container scanning, secret detection, and configuration validation. Security assessment is triggered according to the pipeline stage and the risk profile of the affected components.

3.2.5. Risk Correlation and Decision Layer

This layer combines model predictions with confirmed security findings, vulnerability intelligence, exploitability, application exposure, and business criticality. It generates actionable security decisions.

3.2.6. Continuous Feedback and Governance Layer

The final layer records validated findings, remediation outcomes, false positives, model performance, and policy decisions. This information supports controlled model retraining, auditability, and continuous improvement.



Figure 1. Overall Architecture of the Proposed Intelligent DevSecOps Framework

The architecture establishes a continuous relationship between predictive analysis and automated security testing. Machine learning outputs are used to direct additional assessment, while conventional security scanners provide technical evidence for validating predictions. This two-way relationship prevents the predictive model from becoming an independent and unverified deployment authority.

3.3. Data Collection and Dataset Preparation

The effectiveness of a vulnerability prediction system depends substantially on the quality, completeness, and representativeness of its training data. The proposed research uses multiple categories of software security information to develop a comprehensive dataset.

Historical vulnerability information can be collected from the National Vulnerability Database, GitHub Security Advisories, Open Source Vulnerabilities, security issue trackers, and publicly available vulnerability research repositories. Source code changes associated with reported vulnerabilities can be extracted from corresponding repositories where reliable mappings are available.

Potential datasets for experimental evaluation include Big-Vul, DiverseVul, Devign, and other publicly documented vulnerability datasets. However, these datasets differ in programming language coverage, labeling methodology, vulnerability granularity, and project diversity. They should therefore be evaluated for suitability before being combined.

The data collection process considers the following information categories:

- Source code characteristics, including function length, code complexity, nesting depth, and potentially unsafe programming constructs.
- Development characteristics, including commit frequency, file modification history, change size, and code ownership.
- Dependency characteristics, including package versions, transitive dependencies, known vulnerabilities, and maintenance status.
- Historical security characteristics, including vulnerability records, previous security findings, and remediation history.
- Deployment characteristics, including container configurations, infrastructure definitions, exposed interfaces, and application criticality.

The dataset is organized at multiple levels, including file-level, function-level, and component-level observations. This structure supports different prediction tasks and enables the research to investigate whether finer-grained representations improve security assessment.

A critical methodological consideration is the separation of training and testing information according to time. Vulnerability information discovered after a particular release must not inadvertently appear as a predictive feature for that earlier release. Similarly, code revisions associated with the same vulnerability must not be distributed across training and testing sets in a way that artificially inflates performance.

3.4. Feature Engineering and Selection

Feature engineering converts raw development information into meaningful representations that machine learning algorithms can process.

Source code features describe the structural and behavioral characteristics of software components. These may include cyclomatic complexity, function length, nesting depth, number of parameters, code duplication, and usage of potentially unsafe APIs. Such metrics help identify components that may require closer security inspection.

Development process features capture how software changes over time. Components with frequent modifications, large changes, or repeated security-related fixes may exhibit different vulnerability characteristics from relatively stable components. However, these features must be interpreted carefully because frequent development activity does not independently establish vulnerability. Dependency features provide information about external software components. These include dependency age, version history, vulnerability advisories, transitive dependency depth, package maintenance status, and known security weaknesses.

Security history features include previous vulnerability reports, scanner findings, remediation delays, and recurring weakness categories. These features can help identify repeated security problems within software components.

Table 2. Proposed Feature Categories for Machine Learning-Based Vulnerability Prediction

Feature category	Example features	Purpose	Data source
Source code metrics	Complexity, function length, nesting depth	Identify structurally complex components	Source code analysis
Programming constructs	Unsafe API usage, input handling, memory operations	Identify potentially risky coding patterns	Static analysis
Development history	Commit frequency, change size, modification history	Understand software evolution	Git repositories
Dependency intelligence	Package age, vulnerable versions, transitive dependencies	Assess third-party component risk	SCA and advisory databases
Security history	Previous findings, weakness categories, remediation records	Identify recurring vulnerability patterns	Security repositories
Deployment context	Public exposure, privileges, service criticality	Understand operational security impact	Cloud and infrastructure metadata
Assessment results	SAST, DAST, IaC and container findings	Support model validation and risk correlation	Security assessment tools

Feature selection is performed to remove redundant variables and reduce the possibility of overfitting. Statistical analysis, correlation-based selection, permutation importance, and tree-based feature importance can be used to identify relevant characteristics.

The framework also supports feature normalization when required by the selected algorithm. Categorical features, such as programming language, dependency type, and deployment environment, are encoded using suitable preprocessing techniques.

3.5. Machine Learning Model Development

The proposed framework considers four major machine learning approaches.

3.5.1. Random Forest Classification

Random Forest is selected as a primary baseline model because it can process structured software metrics, identify nonlinear relationships, and provide feature importance information. It combines predictions from multiple decision trees to produce a classification result.

The model can identify patterns involving software complexity, development activity, dependency characteristics, and historical security information. Its relatively straightforward training process makes it suitable for establishing an initial predictive benchmark.

3.5.2. Gradient Boosting Classification

Gradient Boosting builds an ensemble of predictive models sequentially, with later models focusing on errors made by earlier models. It can provide strong classification performance on structured datasets and capture complex relationships among vulnerability-related features.

This approach is particularly relevant when the dataset contains heterogeneous software characteristics and interactions between different feature categories.

3.5.3. Support Vector Machine

Support Vector Machines can classify software components by identifying decision boundaries within the feature space. They are useful for investigating classification problems involving high-dimensional feature representations.

However, their performance may depend on feature scaling, kernel selection, and dataset size. Consequently, SVM is considered a comparative model rather than an assumed universally superior solution.

3.5.4. Deep Learning-Based Code Representation

Deep learning models can learn representations from source code sequences, syntax structures, and semantic information. Token-based neural models, recurrent architectures, and transformer-based code representations can be investigated for identifying complex programming patterns.

Unlike conventional feature-based models, these methods may capture contextual relationships within source code. Nevertheless, they introduce additional computational requirements and may require larger, carefully labeled datasets.

The models are evaluated independently before considering an ensemble approach. An ensemble may combine structured software metrics with learned code representations, allowing the framework to benefit from different information sources.

3.6. Handling Class Imbalance

Software vulnerability datasets commonly contain significantly more non-vulnerable examples than vulnerable examples. This imbalance can cause machine learning models to favor the majority class and produce misleadingly high accuracy values.

The proposed research considers several methods for addressing this problem.

- Class-weighted learning assigns greater importance to vulnerable examples during model training.
- Controlled oversampling increases the representation of minority-class examples.
- Undersampling reduces excessive majority-class representation when sufficient data is available.
- Threshold optimization adjusts classification thresholds according to the operational cost of false negatives and false positives.

Synthetic Minority Over-sampling Technique (SMOTE) may be considered for suitable structured feature datasets, although its application must be restricted to the training partitions. Synthetic examples should not be assumed to represent realistic vulnerable source code.

The evaluation should report precision, recall, F1-score, area under the precision-recall curve, and confusion matrix results. Accuracy alone is insufficient for evaluating vulnerability prediction because missing an important vulnerability may have considerably greater consequences than incorrectly flagging a non-vulnerable component.

3.7. Automated Security Assessment Integration

The proposed framework integrates multiple security testing mechanisms into the CI/CD workflow.

SAST is executed during code analysis and pull request validation. It identifies potentially insecure programming patterns and provides information about affected source code locations.

SCA evaluates direct and transitive dependencies against known vulnerability information. Dependency findings are correlated with the application's actual dependency tree, package versions, and available remediation information.

DAST is performed against executable application environments, particularly during integration and staging. Predictive analysis can help identify components that require additional runtime testing, although the final testing process must be determined by technical coverage and security requirements.

IaC scanning evaluates deployment templates, infrastructure permissions, network exposure, encryption settings, and configuration weaknesses. Container scanning identifies vulnerable packages, insecure image configurations, and unnecessary privileges.

Secret detection examines repositories and build outputs for accidentally exposed credentials, API tokens, private keys, and other sensitive information.

SBOM generation provides a structured inventory of software components and dependencies. The resulting inventory supports dependency tracking, vulnerability correlation, and software supply chain transparency.

3.8. Intelligent Risk Prioritization

A central component of the proposed framework is the intelligent risk prioritization engine. Its purpose is to transform multiple security signals into actionable decisions.

The engine considers five major dimensions:

- Vulnerability propensity: The machine learning model's assessment of the likelihood that a software component contains a vulnerability.
- Technical severity: The severity of confirmed security findings, including available CVSS information.
- Exploitability: Evidence concerning known exploitation, exploit availability, and relevant EPSS information.
- Environmental exposure: Whether the affected component is externally accessible, privileged, or connected to sensitive services.
- Business criticality: The importance of the affected application, service, data, or business process.

These dimensions are correlated through a configurable risk policy. A predictive warning may increase the priority of a security assessment, but it should not automatically be treated as a confirmed vulnerability.

For example, a machine learning model may identify an authentication module as high-risk because of complex input handling and historical patterns. The assessment engine can respond by initiating targeted SAST and DAST tests. If the scanners confirm an exploitable weakness, the finding can trigger a deployment restriction according to organizational policy.

If the scanners do not confirm a vulnerability, the predictive warning can be retained for investigation or monitoring rather than automatically blocking the release.



Figure 2. Machine Learning-Based Vulnerability Prediction and Risk Assessment Workflow

3.9. Automated Security Gates and Deployment Governance

Security gates provide enforcement mechanisms that determine whether software can proceed to subsequent pipeline stages. The proposed framework introduces risk-sensitive gates rather than relying exclusively on a single severity threshold.

A release containing a confirmed critical vulnerability may be blocked automatically. A high-risk vulnerability affecting an externally accessible authentication service may require immediate remediation or formal security approval.

Medium-risk findings may be permitted to proceed when documented mitigation measures, responsible ownership, and remediation deadlines are established. Low-risk observations may be recorded for scheduled remediation without interrupting routine development.

Predictive warnings without technical confirmation should generally trigger additional testing or manual review rather than automatic release rejection. This distinction reduces the possibility of excessive false-positive-driven deployment failures.



Figure 3. Risk-Based Automated Security Gate and Deployment Decision Model

3.10. Model Explainability and Governance

Model explainability is essential because software security decisions can affect release schedules, development productivity, and organizational risk. A predictive model should provide more than a risk category.

Feature importance methods can identify characteristics that contribute to a model's predictions. SHAP-based explanations may be used to investigate the contribution of individual features to particular predictions, while local explanation techniques can help developers understand why a specific file or function was classified as high-risk.

However, explanations should not be interpreted as proof of a vulnerability. They describe model behavior and provide guidance for technical investigation.

Model governance includes version management, training data documentation, validation records, approval processes, performance monitoring, and controlled deployment. The framework should maintain a clear distinction between the version of the predictive model used for an assessment and the version of the application being evaluated.

3.11. Experimental Evaluation Strategy

The proposed framework should be evaluated using historical and temporally separated software vulnerability datasets, followed by controlled integration into representative CI/CD pipelines.

The experimental design should compare three configurations:

- Conventional DevSecOps using standard security scanners and predefined policies.

- Machine learning-based vulnerability prediction operating independently of automated security assessment.
- The proposed integrated intelligent DevSecOps framework combining prediction, assessment, correlation, and policy enforcement.

The comparison should examine predictive performance, detection coverage, false-positive behavior, processing overhead, remediation prioritization, and pipeline execution time.

Temporal validation should be used to investigate whether models can predict vulnerabilities using information available before the relevant vulnerability discovery. Cross-project evaluation should test whether models can generalize beyond their training repositories.

The experimental protocol should also document the programming languages, repository characteristics, vulnerability categories, dataset labeling procedures, model versions, and scanner configurations to ensure reproducibility.

3.12. Evaluation Metrics

The following evaluation indicators are proposed:

Table 3.Comprehensive Evaluation Framework for Automated Vulnerability Detection and Security Governance

Evaluation dimension	Metric	Research purpose
Prediction effectiveness	Precision	Measures the reliability of positive predictions
Vulnerability identification	Recall	Measures the proportion of vulnerable examples identified
Classification balance	F1-score	Evaluates the balance between precision and recall
Ranking effectiveness	PR-AUC	Evaluates predictive ranking under class imbalance
Operational efficiency	Pipeline execution time	Measures security-related processing overhead
Alert quality	False-positive rate	Measures unnecessary vulnerability warnings
Remediation efficiency	Mean time to remediate	Evaluates the time required to resolve confirmed findings
Security coverage	Assessment coverage	Measures the proportion of relevant components assessed
Model reliability	Cross-project performance	Evaluates generalization across software projects
Deployment governance	Policy decision consistency	Evaluates consistency of automated release decisions

The evaluation must report results for each project and model configuration, including confidence intervals where appropriate. Statistical significance testing should be considered when comparing alternative approaches.

4. Results and Discussion

4.1. Analysis of the Proposed Framework

The proposed intelligent DevSecOps framework establishes an integrated approach to software vulnerability prediction and automated security assessment. Its primary advantage is the combination of predictive intelligence with conventional security verification mechanisms. Traditional security tools generally identify weaknesses through predefined rules, known vulnerability signatures, or runtime testing. Machine learning introduces an additional analytical capability by examining software characteristics and historical patterns to identify components that may require more intensive security assessment.

The framework is designed to improve the relationship between security identification and security decision-making. Rather than generating independent alerts, the integrated architecture correlates machine learning predictions with actual assessment findings. This provides a structured mechanism for determining whether a component requires additional testing, immediate remediation, or continued monitoring.

A significant benefit of this architecture is its ability to support earlier security intervention. During code integration, machine learning models can examine newly modified files and identify components exhibiting characteristics associated with historical

vulnerabilities. High-risk components can receive additional static analysis and targeted security testing before the application progresses to later pipeline stages.

However, the effectiveness of this approach depends on the reliability of the training dataset and the ability of the predictive model to generalize across different software environments. A model trained using predominantly Java-based enterprise repositories may not automatically perform effectively on Python-based microservices or low-level C and C++ applications. Therefore, programming language, project characteristics, and development practices must be considered during model training and evaluation.

4.2. Comparative Analysis of Machine Learning Algorithms

The proposed research investigates four machine learning approaches with different computational and predictive characteristics.

Random Forest provides an interpretable baseline for structured software metrics. Its ensemble architecture can capture nonlinear relationships among source code complexity, development history, and dependency information. It is particularly suitable for an initial implementation because it does not require the same level of computational resources as large neural architectures.

Gradient Boosting provides another suitable approach for structured vulnerability datasets. It can progressively improve predictive performance by focusing on incorrectly classified observations. However, hyperparameter selection and training configuration can substantially influence its effectiveness.

Support Vector Machines provide a comparative approach for classification tasks involving high-dimensional feature representations. They can be effective when feature preprocessing and kernel selection are appropriate. Nevertheless, training and inference costs may increase with dataset size, depending on the implementation.

Deep learning models provide opportunities for identifying contextual relationships in source code that are difficult to represent through conventional metrics. They can analyze code sequences and structural representations, potentially supporting more detailed vulnerability prediction. Their limitations include training complexity, dataset requirements, computational cost, and reduced transparency.

No algorithm should be considered universally superior. The final model selection should depend on prediction performance, cross-project generalization, computational efficiency, explainability, and operational suitability.

4.3. Comparison of Conventional and Intelligent DevSecOps

Conventional DevSecOps provides substantial security improvements compared with software delivery processes that rely entirely on manual testing. Nevertheless, the integration of multiple scanning tools does not automatically establish an intelligent security management system.

In conventional implementations, a static analysis tool may identify a potential SQL injection vulnerability, while a dependency scanner identifies an outdated database library. These findings may be processed independently, even though both could affect the same application service.

The proposed framework introduces a correlation mechanism that combines these findings with source code characteristics, application exposure, and historical security information. This enables security teams to understand the broader context of potential weaknesses.

For example, if a payment processing service contains a complex input validation function, depends on a vulnerable library, and is publicly accessible, the integrated risk engine can prioritize the service for additional testing. The resulting decision is based on the combined evidence rather than a single scanner output.

This approach can potentially improve security assessment efficiency by allocating testing resources according to the estimated risk of individual components.

4.4. Expected Improvements in Vulnerability Prediction

The proposed machine learning architecture is expected to improve the identification and prioritization of potentially vulnerable components when compared with approaches that rely exclusively on predefined rules.

One anticipated improvement is the ability to identify security-sensitive components that do not yet generate conventional scanner findings. Historical development characteristics and source code patterns may reveal areas requiring additional examination.

Another anticipated improvement concerns risk-based testing. Instead of performing every possible intensive security assessment against every component during every pipeline execution, organizations can use predictive information to identify areas requiring additional attention.

However, this optimization must not eliminate mandatory security controls. Baseline SAST, SCA, secret detection, artifact validation, and other essential checks should remain active according to organizational security requirements. Machine learning should supplement established security mechanisms rather than replace them.

4.5. Reduction of False Positives and Alert Fatigue

False positives represent an important challenge in automated application security. A scanner may identify a potentially dangerous code pattern even when the relevant execution path is inaccessible or appropriate validation controls are already implemented.

The proposed framework addresses this issue through finding correlation, contextual analysis, and validation.

Machine learning predictions can be used to rank components for additional examination, while security scanners provide technical evidence. When multiple tools identify related weaknesses in the same component, the correlation engine can consolidate the findings and provide a more meaningful security assessment.

Nevertheless, machine learning does not automatically eliminate false positives. Predictive models can introduce additional classification errors, particularly when training data is incomplete or poorly labeled. The appropriate objective is therefore to improve the quality of security decisions and reduce unnecessary investigation rather than claim that all false positives can be removed.

4.6. Optimization of CI/CD Pipeline Performance

Security assessment can introduce additional execution time into CI/CD pipelines. Large source code repositories, extensive dependency trees, and multiple container images may require substantial scanning resources.

The proposed framework introduces selective assessment orchestration to improve resource allocation. Frequently modified components can undergo incremental analysis, while high-risk components can receive additional assessment based on their predictive profiles.

Caching previously analyzed dependency information, using parallel scanning workers, and prioritizing changed components are additional optimization mechanisms.

However, selective scanning must be implemented carefully. A change to a shared authentication library or common infrastructure module may affect several services, even when only one repository file has been modified. Dependency relationships and application architecture must therefore be considered before determining the scope of an assessment.

The proposed system should also measure the additional latency introduced by the prediction service. A model that provides strong predictive performance but significantly delays every build may not be suitable for production environments.

4.7. Software Supply Chain Security Implications

Modern applications frequently incorporate external libraries, container images, build tools, and third-party services. Consequently, vulnerabilities may originate outside the application's internally developed source code.

The proposed architecture integrates dependency analysis, SBOM generation, artifact validation, and vulnerability intelligence into the assessment workflow. This enables organizations to identify potentially affected software components and maintain visibility into their dependencies.

NIST SP 800-204D provides relevant guidance concerning the integration of software supply chain security into CI/CD environments, including artifact integrity, provenance, and software component management (Chandramouli et al., 2024).

The framework also considers the risks associated with the CI/CD platform itself. Build agents, source code repositories, deployment credentials, and pipeline configurations must be protected through least-privilege access, credential rotation, isolation, and appropriate logging.

This is particularly important because an attacker who compromises the delivery pipeline may be able to introduce malicious changes into otherwise legitimate software releases.

4.8. Model Explainability and Developer Acceptance

The successful adoption of predictive security mechanisms depends not only on model performance but also on the ability of developers to understand and act upon predictions.

An automated warning that simply labels a file as high-risk may not provide sufficient information for remediation. Developers need to understand which characteristics contributed to the prediction and which security assessments should be performed.

The proposed architecture therefore integrates explainability into the prediction layer. Feature importance information, code-level references, associated scanner findings, and remediation guidance can be included in the security report.

For example, a prediction may identify a function because of its high complexity, unsafe input processing, and historical vulnerability patterns. The report can direct developers toward the relevant function and recommend additional input validation assessment.

Explainability can improve the practical value of predictive analysis by transforming machine learning outputs into actionable engineering information.

4.9. Comparative Research Findings

The following table summarizes the anticipated differences between conventional security workflows and the proposed framework. These are architectural expectations to be evaluated experimentally, not measured experimental results.

Table 4. Comparative Evaluation of Conventional DevSecOps and the Proposed Intelligent Framework

Evaluation parameter	Conventional DevSecOps	Proposed intelligent DevSecOps
Vulnerability identification	Primarily scanner-based	Scanner-based with predictive analysis
Security prioritization	Severity and predefined rules	Severity, prediction, exposure, and business context
Source code assessment	Static rule-based analysis	Static analysis with ML-based risk guidance
Dependency management	Known vulnerability matching	Dependency matching with contextual prioritization
Security tool integration	Frequently independent outputs	Centralized finding correlation
Testing strategy	Predominantly predefined assessment	Risk-informed assessment orchestration
False-positive management	Manual investigation and suppression	Contextual correlation and validation
Explainability	Scanner-specific descriptions	Model explanations with technical findings
Deployment governance	Static security thresholds	Risk-based automated policy decisions
Continuous improvement	Rule and scanner updates	Rule updates and controlled model improvement
Cross-project adaptability	Depends on tool coverage	Requires model transfer validation
Operational monitoring	Scanner and pipeline logs	Scanner, pipeline, and model monitoring

4.10. Performance Evaluation and Interpretation

A rigorous experimental evaluation is necessary before the framework can be considered empirically validated.

The first evaluation stage should establish baseline results for conventional vulnerability prediction algorithms. Random Forest, Gradient Boosting, Support Vector Machines, and deep learning models should be trained and evaluated using consistent datasets and validation procedures.

The second stage should examine prediction quality under different dataset conditions. These conditions should include balanced and imbalanced data, within-project and cross-project evaluation, and different vulnerability categories.

The third stage should investigate the impact of predictive analysis on security assessment. Researchers should compare the number of components receiving additional security testing, the number of confirmed vulnerabilities identified, the volume of false-positive warnings, and the total pipeline execution time.

The fourth stage should assess operational effectiveness through controlled CI/CD experiments. These experiments should measure whether predictive prioritization improves the allocation of security testing resources without reducing baseline security coverage.

Ablation studies are also recommended. For example, the contribution of source code features, development history, dependency intelligence, and deployment context can be evaluated separately. This will help identify which information categories contribute most significantly to the predictive model.

Finally, statistical significance and practical significance should be evaluated independently. A small improvement in classification performance may not justify additional model complexity if the resulting system introduces substantial deployment delays or maintenance requirements.

4.11. Security and Operational Limitations

Although the proposed framework offers a comprehensive architecture, several limitations require consideration.

The first limitation concerns dataset quality. Public vulnerability repositories do not necessarily provide complete vulnerability labels for all source code components. Missing or incorrect labels can influence training and evaluation outcomes.

The second limitation involves model generalization. Software projects differ in programming languages, architectural patterns, coding standards, and dependency management practices. A predictive model may experience performance degradation when applied to unfamiliar repositories.

The third limitation concerns adversarial manipulation. Attackers may intentionally modify source code characteristics or training information to influence model predictions. Therefore, the prediction service requires secure data ingestion, access control, model integrity validation, and monitoring.

The fourth limitation involves computational overhead. Deep learning models may require additional processing resources, especially when applied to large repositories and frequent commit events.

The fifth limitation concerns automated deployment decisions. An incorrect prediction should not independently authorize insecure deployment or permanently block legitimate software changes. Human oversight and evidence-based security policies remain important.

The final limitation involves the maintenance of vulnerability intelligence. Security advisories, exploitability information, package versions, and application exposure change over time. Consequently, the system must maintain updated information and periodically evaluate the quality of its predictions.

4.12. Overall Research Implications

The analysis indicates that intelligent DevSecOps optimization should be understood as an integration problem rather than an isolated machine learning classification task.

The greatest potential value of the proposed framework comes from connecting predictive vulnerability intelligence with actual security assessment and deployment governance. Machine learning identifies components that may require attention, automated scanners investigate their technical characteristics, and the policy engine determines appropriate actions.

This integrated approach can support more efficient security assessment, better vulnerability prioritization, and improved visibility across the software delivery lifecycle.

Nevertheless, the proposed architecture must be evaluated using real-world repositories and representative CI/CD workloads before quantitative performance improvements can be established. Its effectiveness will depend on the quality of the training data, model selection, scanner coverage, policy configuration, and operational governance.

5. Conclusion

The increasing complexity of contemporary software delivery environments has created a significant requirement for intelligent, continuous, and automated security assessment. Traditional DevSecOps practices have improved software security by integrating static analysis, dependency scanning, runtime testing, infrastructure validation, and deployment controls into CI/CD pipelines. However, the growing volume of software components, external dependencies, and security findings has created challenges involving vulnerability prioritization, assessment efficiency, and continuous risk management.

This research proposed an intelligent DevSecOps optimization framework that combines machine learning-based vulnerability prediction with automated security assessment across the software development lifecycle. The framework integrates historical vulnerability information, source code characteristics, development activity, dependency intelligence, and deployment context to identify potentially vulnerable software components.

The proposed architecture incorporates Random Forest, Gradient Boosting, Support Vector Machines, and deep learning-based code representations to investigate different vulnerability prediction approaches. These models provide predictive information that can guide additional security assessment through SAST, SCA, DAST, IaC scanning, container security analysis, and secret detection.

A major contribution of the proposed framework is the integration of predictive intelligence with contextual risk prioritization. Rather than relying exclusively on conventional vulnerability severity classifications, the framework considers exploitability, application exposure, asset criticality, and confirmed assessment findings. This enables security teams to make more informed decisions regarding remediation, monitoring, escalation, and deployment approval.

The research also emphasizes the importance of explainability, data quality, cross-project generalization, model monitoring, and secure CI/CD infrastructure. Predictive outputs must remain distinguishable from confirmed vulnerabilities, and machine learning should complement rather than replace established security testing mechanisms.

From an architectural perspective, the proposed framework establishes a foundation for moving from reactive vulnerability detection toward predictive and preventive security management. It provides a structured approach for integrating artificial intelligence into DevSecOps while maintaining the importance of conventional security controls, human oversight, and organizational governance.

Although the proposed methodology establishes the technical foundation for implementation, quantitative improvements must be demonstrated through empirical experiments involving real-world repositories and CI/CD pipelines. Future experimental validation should determine whether the integrated architecture can improve prediction quality, assessment efficiency, remediation prioritization, and deployment security without introducing unacceptable operational overhead.

Overall, intelligent DevSecOps optimization represents a promising direction for developing secure, scalable, and continuously assessed software delivery environments.

6. Future Scope

The proposed research provides several opportunities for further investigation and technological development.

6.1. Integration of Large Language Models for Vulnerability Analysis

Future implementations can investigate Large Language Models (LLMs) for contextual source code analysis, security code review, and remediation recommendation generation. Unlike conventional structured feature-based models, LLMs can examine programming logic, interpret code context, and explain potentially insecure implementations.

An LLM-based component could assist developers in understanding why a particular function has been identified as high-risk and suggest secure implementation alternatives. However, generated recommendations must be validated through static analysis, testing, and secure development review rather than accepted automatically.

6.2. Advanced Deep Learning-Based Vulnerability Prediction

Future research can investigate transformer-based code models, graph neural networks, and hybrid neural architectures for identifying complex vulnerability patterns. These approaches may provide improved representations of program dependencies, control flow, data flow, and semantic relationships.

Graph-based models are particularly interesting because software applications contain interconnected functions, classes, services, and dependencies. Analyzing these relationships may help identify vulnerabilities whose security implications extend beyond individual source files.

6.3. Real-Time Predictive Security Assessment

An important future direction is the implementation of real-time vulnerability prediction during code commits and pull requests. Instead of waiting for the complete CI/CD pipeline to execute, predictive services could analyze modified components immediately and provide developers with early security feedback.

This approach could support more efficient remediation by identifying potentially risky changes before they become integrated into larger application releases.

6.4. Autonomous Security Remediation

Future implementations can investigate controlled automation for vulnerability remediation. Intelligent systems may recommend secure code modifications, dependency upgrades, configuration corrections, and infrastructure policy changes.

Autonomous remediation should operate under strict validation requirements. Proposed modifications must undergo testing, security verification, code review, and appropriate approval before deployment.

6.5. Explainable and Trustworthy AI for Cybersecurity

Further research is required to improve the interpretability of machine learning-based security decisions. Future systems should provide evidence explaining the characteristics responsible for vulnerability predictions and the reasons behind automated deployment restrictions.

The integration of explainable AI with security audit trails can improve transparency, developer acceptance, and regulatory accountability.

6.6. Cross-Project and Cross-Language Model Generalization

Future research should investigate whether vulnerability prediction models trained on one software ecosystem can perform effectively across different repositories and programming languages.

Transfer learning, domain adaptation, language-specific feature representations, and federated learning may provide opportunities to improve model adaptability while addressing data privacy requirements.

6.7. Federated Learning for Enterprise Security Intelligence

Organizations may be reluctant to share source code and internal vulnerability information because of confidentiality and intellectual property requirements. Federated learning could provide an alternative approach in which participating organizations collaboratively improve predictive models without directly sharing their underlying training datasets.

Further investigation is required to address model poisoning, privacy leakage, secure aggregation, and differences in vulnerability distributions between participating organizations.

6.8. Integration with Software Supply Chain Security

Future frameworks can extend predictive security analysis to software artifacts, package repositories, build environments, container registries, and deployment infrastructure.

Integration with SBOM standards, artifact signing, provenance verification, and supply chain security frameworks can improve software component visibility and establish stronger assurance throughout the software delivery process.

6.9. Empirical Enterprise-Level Validation

A particularly important future research direction is the implementation and validation of the proposed framework in enterprise CI/CD environments.

Experiments should involve representative repositories, multiple programming languages, cloud-native applications, and real-world security assessment tools. Performance should be evaluated using prediction quality, security coverage, false-positive rates, pipeline latency, remediation time, and cross-project generalization.

Such validation would establish the practical applicability of the framework and provide measurable evidence of its contribution to intelligent DevSecOps optimization.

References

[1] Bassi, D., & Singh, H. (2023). A systematic literature review on software vulnerability prediction models. *IEEE Access, 11*, 110289–110311. https://doi.org/10.1109/ACCESS.2023.3312613

[2] Gali, V. K., & Eruvuru, B. K. (2023). AI-Assisted Continuous Controls Monitoring (CCM) in Oracle Cloud ERP: An Intelligent and Adaptive Framework for Enterprise Compliance. International Journal of AI, BigData, Computational and Management Studies, 4(4), 138-146. https://doi.org/10.63282/3050-9416.IJAIBDCMS-V4I4P115

[3] Chandramouli, R., Kautz, F., & Torres-Arias, S. (2024). *Strategies for the integration of software supply chain security in DevSecOps CI/CD pipelines* (NIST Special Publication 800-204D). National Institute of Standards and Technology. https://doi.org/10.6028/NIST.SP.800-204D

[4] Savaliya, J. (2020). A Multi-Dimensional Test Automation Framework for Embedded Wireless Platforms: Configuration Modeling and Regression Testing. *International Journal of Emerging Trends in Computer Science and Information Technology*, *1*(1), 82-94. https://doi.org/10.63282/3050-9246.IJETCSIT-V1I1P110

[5] Chowdhury, M. N.-U.-R. (2023). A catalog of metrics at source code level for vulnerability prediction: A systematic mapping study. *Journal of Software: Evolution and Process, 36*(7), e2639. https://doi.org/10.1002/smr.2639

[6] Kalouptsoglou, I., Siavvas, M., Ampatzoglou, A., Kehagias, D., & Chatzigeorgiou, A. (2023). Software vulnerability prediction: A systematic mapping study. *Information and Software Technology, 164*, 107303. https://doi.org/10.1016/j.infsof.2023.107303

[7] National Institute of Standards and Technology. (2022). *Secure software development framework (SSDF) version 1.1: Recommendations for mitigating the risk of software vulnerabilities* (NIST Special Publication 800-218). U.S. Department of Commerce. https://doi.org/10.6028/NIST.SP.800-218

[8] Gali, V. K. (2022). Governance Framework Approach for Oracle Cloud ERP: Secure and Scalable Enterprise Governance. International Journal of Emerging Research in Engineering and Technology, 3(3), 136-147. https://doi.org/10.63282/3050-922X.IJERET-V3I3P114

[9] OWASP Foundation. (n.d.). *CI/CD security cheat sheet*. OWASP Cheat Sheet Series. https://cheatsheetseries.owasp.org/cheatsheets/CI_CD_Security_Cheat_Sheet.html

[10] OWASP Foundation. (n.d.). *OWASP DevSecOps guideline*. https://owasp.github.io/DevSecOpsGuideline/

[11] OWASP Foundation. (n.d.). *OWASP Top 10 CI/CD security risks*. https://owasp.org/projects/top-10-cicd-security-risks

[12] Gali, V. K. (2021). Cash Flow and Working Capital Optimization Using Oracle Fusion ERP/EPM Data. International Journal of Emerging Research in Engineering and Technology, 2(4), 80-89. https://doi.org/10.63282/3050-922X.IJERET-V2I4P109
[13] National Institute of Standards and Technology. (n.d.). *DevSecOps*. National Cybersecurity Center of Excellence. https://pages.nist.gov/nccoe-devsecops/
[14] Gali, V. K. (2021). Predictive Forecasting and Strategic Approach in Oracle Fusion ERP: Intelligent Planning Models. *International Journal of AI, BigData, Computational and Management Studies*, 2(3), 82-92. https://doi.org/10.63282/3050-9416.IJAIBDCMS-V2I3P110.